



panel mount



desktop version

- 85 keys, silicone rubber
- IP67 sealing
- 38 mm ergonomic trackball

RKTE85

COMPACT RUBBER KEYBOARD WITH ERGONOMIC TRACKBALL

This 85 key backlit keyboard features a compact keyboard with integrated waterproof 38 mm ergonomic trackball with scroll wheel. The rubber keys are proven for efficient cleaning, reduced disinfection time and protection against cross contamination. The backlit keys warrant for optimized performance while working in low-light environments. Panel mount and desktop version available.

MAIN FEATURES

- Compact layout, 85 full travel keys
- 38 mm waterproof ergonomic trackball with hall-effect scroll wheel
- Removable ball for easy cleaning
- Dimmable backlighting at 8 levels by two dedicated keys (FN kev + arrow up/down)
- · No external power supply necessary, keyboard port power sufficient
- · Low power LED's warrant for a long life
- · White backlighting as standard, other colours on request
- Compact thickness

PANEL MOUNT VERSION

- Front panel mounting with M3 stud, 10 x M3 x 15 mm
- Dimensions: 415 x 145 x 79 mm
- Weight: 0,7 kg

DESKTOP VERSION

- ABS enclosure
- Dimensions: 420 x 150 x 68,22 mm
- Weight: 1,2 kg

CUSTOMIZATION

Possible customization includes adapted backlighting controls, addition of company logo or specific function keys, different layouts, different colour.

GENERAL TECHNICAL SPECIFICATIONS

KEYBOARD Sealing

Keys Pointing device Output **Power requirements** Operating temp. Storage temp. Switch force Switch stroke Lifetime switches

TRACKBALL **Ball size/material**

Tracking force Ball load

Tracking engine

Removable ring

Wheel diameter

Wheel material

Magnet strength

Wheel colour

Resolvable ball speed

SCROLL WHEEL

Encoding technology

Dentent-scrolling force

Switch actuation force

LEFT/RIGHT SWITCH Switch actuation force

85 full travel rubber keys 38 mm ergonomic trackball 1,6 m USB cable Directly from USB port -15°C to +70°C -40°C to +85°C 300 grams ± 100 grams 1.5 mm 1 million actuations

IP67 sealed frontal

Ø38,1 mm (1.5")/Epoxy resin 30 - 80 grams - PTFE seal 100N (10 kg) maximum downward pressure for 2 minutes @ 20°C 30 IPS (inches per second) Infra-red optical navigation technology PC/ABS, black

Ø25 mm PC/ABS Grey Hall effect N42



30 grams nominal 275 ± 125 grams force

 250 ± 100 grams force

ORDER INFO

COUNTRY LAYOUT	PANEL MOUNT	DEKSTOP VERSION
US Qwerty	RKTE85B0001-WLED	RKTE85S0001-WLED
Cyrillic Qwerty	RKTE85B0007-WLED	RKTE85S0007-WLED
French Azerty	RKTE85B0033-WLED	RKTE85S0033-WLED
Danish Qwerty	RKTE85B0045-WLED	RKTE85S0045-WLED
German Qwertz	RKTE85B0049-WLED	RKTE85S0049-WLED

USB output

White backlighting as standard, other colours on request

VER 1 - 2023 09 The company reserves the right to alter without prior knowledge the specification or design of any standard product or service

NSI bv • Kapittelstraat 18 • 3740 Bilzen • Belgium +32 (0)89 51 90 00 • info@nsi-be.com


ISO 9001 ISO 14001

p1/3



DIMENSIONAL DRAWING

PANEL MOUNT



p 2/3 The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.



DIMENSIONAL DRAWING

DESKTOP

