

- 38 mm waterproof trackball
- IP65 sealing

MEMBRANE IP65 KEYBOARD WITH TRACKBALL

The unit features a full MF (multi-functional) keyboard with separate numeric-, cursor- and control keypads. The robust industrial grade trackball has a ball diameter of 38 mm and allows highest precision in cursor control. The keyboard part is sealed to IP65, the self-adjusting PTFE seal of the trackball enables an IP65 static (ball in rest) protection grade. Colour scheme and legend styling fit with the most recent industrial computer equipment.

MAIN FEATURES

Sealing to IP65

- 106 membrane keys with tactile feel, 1,4 mm travel and 4N operating force
- Integrated 38 mm laser optical trackball with removable ball

PANEL MOUNT VERSION

- Front of panel mounting by eight M4 mounting studs
- Metal protection covers on the backside protect the mechanical- and electronical components.
- Added silicon sponge seal for perfect sealing into the user's panel
- Dimensions: 396 x 180 x 44/32 mm
- Weight: 1,3 kg

DESKTOP VERSION

- Keyboard is housed in a robust steel enclosure
- Will fit into 19" rack drawers (1HU) or can be used as desktop model
- Dimensions: 410 x 204 x 42 mm
- Weight: 2,3 kg

GENERAL TECHNICAL SPECIFICATIONS

KEYBOARD Sealing Keys Pointing device Output Power requirements Operating temp. Front layer

IP65 sealed 106 tactile membrane keys 38 mm trackball 1,6m PS/2 or USB cables Directly from PS/2 or USB port 0°C to +60°C Black polyester front layer with embossed keys, scratch and chemical resistant

CONNECTIVITY

The PS/2 keyboards are supplied with one 1,6 m long shielded straight cable ended with 6 pin mini DIN plugs. The USB versions are supplied with one 1,6m long shielded straight cable ended by a USB type A connector.

ORDER INFO

COUNTRY LAYOUT	Panel mount	DEKSTOP VERSION
US Qwerty	KBMT106F1xxx	KBMT106S1xxx
French Azerty	KBMT106F33xxx	KBMT106S33xxx
Swedish Qwerty	KBMT106F46xxx	KBMT106S46xxx
German Qwertz	KBMT106F49xxx	KBMT106S49xxx

xxx = protocol output: USB or PS/2 output

p 1 / 3 VER 1 - 2023 10

NSI bv • Kapittelstraat 18 • 3740 Bilzen • Belgium +32 (0)89 51 90 00 • info@nsi-be.com

www.nsi-be.com

The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.

ISO 9001 ISO 14001






DIMENSIONAL DRAWING

PANEL MOUNT



-M4x25





COLOURS

- Keyboard backgroud: RAL 7035 light grey
- Keys edges: RAL 7037 dustry grey
- Key legends: RAL 9005 jet black

p 2 / 3 VER 1 - 2023 10

The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.






DIMENSIONAL DRAWING







COLOURS

- Metal enclosure: RAL 7037 dusty grey
- Keyboard background: RAL 7035 light grey
- Key edges: RAL 9037 dustry grey
- Key legends: RAL 9005 jet black

p 3/3 The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.